

## CLAIMS

1. An infant garment, comprising:
  - (A) a body made of sheet material;
  - (B) left and right loop fasteners, attached to upper left and right corners of an inside surface, respectively, adjacent to an upper rear edge of a back portion of the body made of sheet material;
  - (C) a front loop fastener strip carried by an outer surface adjacent to an upper edge of a front portion of the body made of sheet material; and
  - (D) left and right fastener extensions connecting left and right ends of the front loop fastener strip to the left and right loop fasteners, respectively.
  
2. The infant of claim 1, additionally comprising:
  - (A) left and right outside rear fastening patches, having loop surfaces, carried by an outside surface of the back portion of the body made of sheet material; and
  - (B) left and right auxiliary fasteners attached to a middle portion of the left and right fastener extensions, respectively, wherein each auxiliary fastener includes a first surface having hook fasteners and a smooth second surface, and wherein the hook fasteners of the first surface of the left and right auxiliary fasteners are attachable to the loop surfaces of the left and right outside rear fastening patches, respectively.

FOUO T-952/650

3. A garment for wear by an infant, comprising:
  - (A) a body made of sheet material;
  - (B) left and right loop fasteners, attached to upper left and right corners of an inside surface, respectively, adjacent to an upper rear edge of a back portion of the body made of sheet material;
  - (C) a front loop fastener strip carried by an outer surface adjacent to an upper edge of a front portion of the body made of sheet material;
  - (D) left and right fastener extensions connecting left and right ends of the front loop fastener strip to the left and right loop fasteners, respectively;
  - (E) left and right outside rear fastening patches, having loop surfaces, carried by an outside surface of the back portion of the body made of sheet material; and
  - (F) left and right auxiliary fasteners attached to a middle portion of the left and right fastener extensions, respectively, wherein each auxiliary fastener includes a first surface having hook fasteners and a smooth second surface, and wherein the hook fasteners of the first surface of the left and right auxiliary fasteners are attachable to the loop surfaces of the left and right outside rear fastening patches, respectively.